CHEMICALS: None Required

EQUIPMENT: Personal Protective Equipment (goggles, gloves)

Wet Floor Signs Dust Mop


Burnishing Machine

Buffing Pad Broom & Dust Pan

PROCEDURES:

STEPS KEY POINTS

- 1. Assemble equipment.
- Remove any freestanding objects from the floor.



1. See above.

 Place "Caution-Wet Floor" signs at the end of each area. Place walk-off mat at exit area.

Note: Floor must be cleaned prior to any burnishing using an appropriate cleaning program as described in cleaning section. The floors must be free of loose soils before buffing to insure that the dirt is not "buffed" into the finish.

 Dust mop the entire floor and remove any dry soil or dust using an untreated mop.



 Dust mopping floor will reduce damage to film caused by the dirt during the burnishing process.

- 4. Fit an appropriate pad to the burnishing machine.
- Make steady pass over the area with burnishing machine. Repeat if desired result is not obtained with one pass.



- Pad selection will be dependent on the finish used, the machine speed and weight.
- Do not allow burnishing machine to stand idle while running as it will "burn" a hole (doughnut) in the finish.

 Dust mop entire floor and remove all dry soil.
Remove wet floor signs.



6. Work toward ends of aisles, pick up with dust pan and broom. Return any furniture moved.

7. Clean all equipment and return to its appropriate area.



7. Equipment in good clean working order improves the quality of the result.