

CHEMICALS: REVEAL diluted 1:40


EQUIPMENT:

Personal Protective Equipment (goggles, gloves)
Tape
Wet Floor Signs
Dust Mop
Putty Knife or Edging Tool
Mop Bucket with Wringer

Clean cotton mop for rinse
Autoscrubber
Blue Cleaning Pads
Burnishing Machine & pads
Broom & Dust Pan
Wiping Cloths

PROCEDURES:

STEPS	KEY POINTS
1. Assemble equipment.	1. See above.
2. Remove any free-standing objects from the floor. Vacuum or clean the walk-off mats and set aside.	2. Place "Caution-Wet Floor" signs at the end of each area. Place walk-off mat at exit area.
3. Remove gum and other material with putty knife. Tape edge if this area meets another tile or carpet area.	3. Deposit in waste receptacle. 4. Work toward ends of aisles, pick up with dust pan and broom.
4. Dust mop entire floor and remove all dry soil.	
5. Wearing appropriate safety equipment according to product label directions.	5. Local site OH&S requirements may require specific chemical handling.
6. If the cleaner is not automatically dispensed, fill the solution tank of the scrubber according to label directions with cool water.	6. Use of hot water will soften polish and risk film failure or yellowing due to dirt embedment.
7. Scub floor with autoscrubber machine fitted with blue cleaning pads. Make first pass with solution valve open pads down, squeegee	7. Make slow overlapping passes with machine. Work from areas already cleaned to minimise slipping on floor. Change pads and



up and vacuum off.
Second pass with pads
down and vacuum on.



rinse as they become
full for reuse.

8. Make second pass with
solution valve open
pads down, squeegee
down and vacuum on.



8. Do not allow the floor to
dry before picking up
the soiled cleaner
solution.

9. Apply clean rinse water
from the tank with pads
down and vacuum on.

10. Trail mop autoscrubber
with rinse water to
remove any areas
missed by squeegee.

11. Allow floor to dry to
touch



9. Do not use hot water to
speed dry time or film
damage could occur.

10. Make sure to mop over
areas that are streaked
from autoscrubber.

11. Check for areas where
dirty film remain.
Repeat steps 7 - 10 on
any spots not
completely cleaned.

12. Check for powder
residue on the floor with
palm of hand.

13. Burnish floor with an
appropriate pad and
machine.

14. Dust mop entire floor
and remove all dry soil.




12. White powder on palm
indicates insufficient
rinsing. Repeat steps
9 - 10 again.

13. Burnishing the floor will
give a fast start to the
gloss result of the
recoat.

14. Work toward ends of
aisles, pick up with dust
pan and broom.

15. Clean all equipment
and return to its
appropriate area.
Remove wet floor signs.



15. Equipment in good
clean working order
improves the quality of
the result.