





CHEMICALS: SNAPBACK use at 1:30

EQUIPMENT: Personal Protective Equipment (goggles, gloves)
Wet Floor Signs
Dust Mop
Clean Rayon Mop and Wringer bucket
Autoscrubber
Buffing Pad
Broom & Dust Pan

PROCEDURES:

STEPS		KEY POINTS
1. Assemble equipment. 2. Remove any free-standing objects from the floor. Vacuum or clean the walk-off mats and set aside.		1. See above. 2. Place "Caution-Wet Floor" signs at the end of each area. Place walk-off mat at exit area.
Note: If soiling is heavy, perform routine maintenance procedures as described in cleaning section. The floor must be free of gross soils before restoring to insure that the dirt is not "buffed" into the finish.		
3. If the cleaner maintainer is not automatically dispensed, fill the solution tank of scrubber according to label directions with cool water.		3. Do not use hot water or damage to floor coating may occur. Wear appropriate safety equipment when handling chemicals.
4. Make one pass over the area with pads down, solution valve open and squeegee down.		4. Change the cleaning solution when it becomes heavily soiled if using a recycle system.
5. Trail mop areas missed by the scrubber using maintainer solution diluted in water in wringer bucket. Allow to fully dry on floor.		5. Change trail mop solution when soiled. Do not buff floor until maintainer has dried or hazing of the finish will result.
6. Buff floor using machine with buffing pad.		6. Turn pad and clean as pad begins to collect particles and dried maintainer.

7. Clean all equipment and return to its appropriate area.



7. Equipment in good clean working order improves the quality of the result.

8. Dust mop entire floor and remove all dry soil. Remove wet floor signs.



8. Work toward ends of aisles, pick up with dust pan and broom. Return any furniture moved.