





CHEMICALS: SNAPBACK use at 1:4

EQUIPMENT: Personal Protective Equipment (goggles, gloves)
Wet Floor Signs
Dust Mop
Labelled Spray Bottles
Rotary Floor Machine -Low Speed
Red Buffing Pad
Broom & Dust Pan

PROCEDURES:

STEPS	KEY POINTS	
<ol style="list-style-type: none"> 1. Assemble equipment. 2. Remove any free-standing objects from the floor. Vacuum or clean the walk-off mats and set aside. 		<ol style="list-style-type: none"> 1. See above. 2. Place "Caution-Wet Floor" signs at the end of each area. Place walk-off mat at exit area.
<p>Note: Before spray buffing perform routine maintenance procedures as described in cleaning section. The floor must be free of gross soils before spray buffing to insure that the dirt is not "buffed" into the finish.</p>		
<ol style="list-style-type: none"> 3. Attach a red buffing pad to floor buffing machine. 4. Apply spray buff in a fine mist using a labelled spray bottle. Do not over use the product. 		<ol style="list-style-type: none"> 3. Pads maybe different depending on the finish & the repair needed for the floor. 4. Applying more spray buff than necessary will result in hazing of the finish.
<ol style="list-style-type: none"> 5. Make at least three passes over the spray buff area. Work in managable sized areas. 		<ol style="list-style-type: none"> 5. Turn pad and clean as pad begins to collect particles and dried spray buff.
<ol style="list-style-type: none"> 6. Clean all equipment and return to its appropriate area. 7. Dust mop entire floor and remove all dry soil. Remove wet floor signs. 		<ol style="list-style-type: none"> 6. Equipment in good clean working order improves the quality of the result. 7. Work toward ends of aisles, pick up with dust pan and broom.