

## PROCEDURES

## FLOORCARE F1 STRIPPING SINGLE DISK

#### CHEMICALS:

PRONTO use at 1:4

PADS:


Black

EQUIPMENT: Personal Protective Equipment (goggles, gloves) Wet Floor Signs Dust Mop Putty Knife or Edging Tool 2 Mop Buckets with Wringers Cotton Mop to apply stripper

### **PROCEDURES:**

## STEPS

- 1. Assemble equipment
- 2. Remove any freestanding objects from the floor. Vacuum or clean the walk-off mats and set aside
- Remove gum and other material with putty knife. Tape edge if this area meets another tile or carpet area.
- 4. Dust mop entire floor and remove all dry soil.
- Wearing appropriate safety equipment according to product label directions.
- 6. Mix stripper per label dilution. **Note:** Add chemical to water and never leave chemicals unattended.
- 7. Ensure adequate ventilation is present.
- 8. Using mop and bucket apply stripper liberally to the floor.













Clean cotton mop for rinse Rotary Floor Machine -Low Speed Broom & Dust Pan Wet Pick-up Vacuum Wiping Cloths

### **KEY POINTS**


- 1. See above.
- 2. Place "Caution-Wet Floor" signs at the end of each area. Place walk-off mat at exit area.
- 3. Deposit in waste receptacle.
- 4. Work toward ends of aisles, pick up with dust pan and broom.
- Local site OH&S requirements may require specific chemical handling
- Use warm to hot water to soften old polish build-up unless label instructions require cold.
- Open windows or mechanically ventilate area.
- 8. Areas may require Taping to prevent stripper migration

© Copyright Johnson Wax Professional. Page 1 Issued 1/11/00



## PROCEDURES

- 9. Allow stripper to stay on floor for 5-10 minutes.
- 10. Use edging tool to strip close to baseboards and in corners.
- 11. Scrub floor with single disk floor machine and Selected stripping pad.







- Keep floor wet, apply more stripper solution if required.
- 10. Attention is required in any areas inaccessible to machine.
- 11. Make slow overlapping passes with machine. Work from areas already stripped to minimise slipping on floor. Change pads and rinse as they become full for reuse.

# NOTE: Remember not to allow stripper to dry on floor, so do not get too far ahead of the floor machine before picking up the stripper.

- 12. After scrubbing, pick up stripper solution with a wet vacuum or mop.
- 13. Apply rinse water with clean rinse mop.
- 14. Pick up rinse water with a wet vacuum or clean mop.
- 15. Wring rinse mop dry and mop over the floor.
- 16. Allow floor to dry to touch
- 17. Check for stripper residue on the floor with palm of hand.
- Clean all equipment and return to its appropriate area. Remove wed floor signs.







- 12. Work from dry area to wet and away from vacuum to avoid tangling cord.
- 13. Hot water will speed dry time.
- Amount of rinsing required will be dependant on stripper used.
- 15. Make sure to mop over areas that are streaked from wet vacuum.
- Check for dark or shiny spots of old finish. Repeat steps 8 - 14 on any spots not completely stripped.
- 17. White powder on palm indicates insufficient rinsing. Repeat steps 13 17 again.
- Equipment in good clean working order improves the quality of the result.

Any questions call Customer Service AUS 1800 807 267 NZ 0800 656 534 © Copyright Johnson Wax Professional. Page 2 Issued 1/11/00