

Material Safety Data Sheet



1. IDENTIFICATION

Product Name: Tonizone Prewash Eucalyptus Spray
Pack Size: 300g
Manufacturer's Code: 306001

UN Number: 1950
Proper Shipping Name: Aerosols

Supplier: Multi-Fill Pty. Ltd.
A.C.N.: 053 439 080
Street Address: 14 Garling Rd.
Kings Park, 2148
NSW Australia

Telephone: +61 2 9621 6000
Facsimile: +61 2 9831 2635

Emergency Telephone Number: No emergency telephone number available.

2. HAZARDS IDENTIFICATION

HAZARDOUS AND DANGEROUS ACCORDING TO THE CRITERIA OF NOHSC and ADGC

The product is classified as Dangerous Goods Class 2.1, by the criteria of the Australian **Dangerous** Goods Code for transport by road and rail.

Hazardous according to the criteria of NOHSC

F+ Extremely Flammable

Xn: Harmful

R12 Extremely flammable

R38 Irritating to skin

R41 Risk of serious eye damage

R65: May cause lung damage if swallowed (highly unlikely in an aerosol form)

R66: Repeated exposure may cause skin dryness or cracking.

S02 Keep out of the reach of children

S03 Keep in a cool place

S15 Keep away from heat

S16 Keep away from sources of ignition - No smoking

S21 When using do not smoke

S23 Do not breathe gas/fumes/vapour/spray

S24 Avoid contact with skin

S25 Avoid contact with eyes

S26: In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre. Phone 13 11 26.

S38 In case of insufficient ventilation, wear suitable respiratory equipment

S47 Keep at temperature below 50 ° C

S62: If swallowed do **NOT** induce vomiting, seek medical advice immediately (contact a doctor or Poisons Information Centre. Phone 13 11 26) and show this container or label.

S63 In case of accident by inhalation: remove casualty to fresh air and keep at rest.

“CAUTION: HIGHLY FLAMMABLE. KEEP OUT OF REACH OF CHILDREN. PRESSURISED DISPENSER. USE IN A WELL VENTILATED AREA. DO NOT INHALE MIST. AVOID CONTACT WITH SKIN. PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50°C. DO NOT PIERCE OR BURN CAN, EVEN AFTER USE. DO NOT SPRAY ON NAKED FLAME OR ANY INCANDESCENT MATERIAL. KEEP AWAY FROM SOURCES OF IGNITION – NO SMOKING. WARNING: Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. PROPELLANT: HYDROCARBON.”

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Entity	CAS Number	Proportion (% w/w)
Iso Parafinic Hydrocarbon	64742-48-9	30-60
C12-C15 Alcohols	68131-39-5	<15
N-(n-dodecyl-2-pyrrolidone)	2687-96-9	<1
Propane/Butane	74-98-6/106-97-8	30-60
Non-hazardous Substances	-	<10

All the constituents of this material are listed on the Australian Inventory of Chemical Substances

4. FIRST AID MEASURES

Skin: Wash contaminated skin with plenty of soap and water. Remove contaminated clothing and wash before re-use. If irritation occurs seek medical advice.

Eyes: Irrigate with copious amounts of water for 15 minutes. In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre. Phone 13 11 26.

Inhalation: Remove victim from exposure – avoid becoming a casualty. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing is laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through facemask. If breathing has stopped, apply artificial respiration at once. In event of cardiac arrest, apply external cardiac massage. Seek medical advice.

Ingestion: Give a little water to drink. **Do NOT induce vomiting.** Avoid giving milks, oils or alcohol. Seek medical advice

Advice to doctor – treat symptomatically.

5. FIRE FIGHTING MEASURES

Specific hazards: Aerosol cans may rupture or explode when exposed to temperatures above 50°C. Propellant is extremely flammable and heavier than air. Do not allow vapours to build up in pits or hollows.

Fire fighting further advice: Fight fire from protected position or use unmanned hose holders or monitor nozzles. If safe to do so, move undamaged containers from fire area. Do not approach hot containers. Cool containers with water before handling. If impossible to extinguish fire, protect surroundings, withdraw from area and allow fire to burn

Fire-fighters to wear self-contained breathing apparatus (SCBA) and protective gloves. Structural fire-fighter's uniform provides limited protection.

Suitable extinguishing media: For small fires use water spray, dry chemical or carbon dioxide
For large fires use water spray or fog

Additional Information: The product is a **UN1950** and has a **HAZCHEM CODE : 2YE**

6. ACCIDENTAL RELEASE MEASURES

Eliminate all sources of ignition. Contain spill for disposal. Add absorbent (sand, earth, sawdust, etc.) to spill area. Keep out of drains and waterways. Dispose of adsorbed material at an approved disposal site according to local government regulations. Ventilate confined spaces well.

7. HANDLING AND STORAGE

Storage: Store away from oxidising agents. Do not store above 50°C. Do **NOT** allow cartons to become wet. Classified as Class 2.1(Aerosols) for the purpose of storage and handling, in accordance with the requirements of AS 2278. Refer to State and Territory Dangerous Goods regulations.

Handling:

No adverse health effects are expected if the product is handled in accordance with this Safety Data sheet and product label. Label states: “**CAUTION: HIGHLY FLAMMABLE. KEEP OUT OF REACH OF CHILDREN. PRESSURISED DISPENSER. USE IN A WELL VENTILATED AREA. DO NOT INHALE MIST. AVOID CONTACT WITH SKIN. PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50°C. DO NOT PIERCE OR BURN CAN, EVEN AFTER USE. DO NOT SPRAY ON NAKED FLAME OR ANY INCANDESCENT MATERIAL. KEEP AWAY FROM SOURCES OF IGNITION – NO SMOKING. WARNING:** Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. **PROPELLANT: HYDROCARBON.**”

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National occupational exposure limits

The assigned value for this product is TWA 1200 mg/cubic meter (171ppm) as per MSDS for Solvent . Propane is an Asphyxiant. Butane TWA is 800 ppm

Engineering measures

Use explosion proof equipment. Use only in a well ventilated area. Do **NOT** use near naked flames.

Personal Protection

At all times protect eyes and avoid direct contact with eyes. In a work environment wear gloves.

Flammability

Use in well ventilated areas. Do **NOT** use near ignition sources.

9. PHYSICAL AND CHEMICAL PROPERTIES

Use: Use to remove stains off clothing

Appearance: Dispenses as an aerosol spray into a turbid liquid with eucalyptus/citrus odour.

Flashpoint: -62°C

Flammability Limits: 9.6% (upper)
1.9% (lower)

Boiling Point (°C): Not Applicable

Solubility in Water: Insoluble

Pressure (25°C): 300 – 400kPa

Specific Gravity: 0.78/mL

10. STABILITY AND REACTIVITY

Propellant can react with oxidising agents – chlorine, pool chlorine and nitric acid. Store away from oxygen cylinders, oxidising materials and ignition sources.

11. TOXICOLOGICAL INFORMATION

“CAUTION: HIGHLY FLAMMABLE. KEEP OUT OF REACH OF CHILDREN. PRESSURISED DISPENSER. USE IN A WELL VENTILATED AREA. DO NOT INHALE MIST. AVOID CONTACT WITH SKIN. PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50°C. DO NOT PIERCE OR BURN CAN, EVEN AFTER USE. DO NOT SPRAY ON NAKED FLAME OR ANY INCANDESCENT MATERIAL. KEEP AWAY FROM SOURCES OF IGNITION – NO SMOKING. WARNING: Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. PROPELLANT: HYDROCARBON.”

Acute Effects

Skin contact: Contact with skin may result in mild irritation

Eye contact: An eye irritant

Inhalation: Vapour is a mild irritant. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of coordination and impaired judgement.

Ingestion: Ingestion can result in nausea, vomiting and diarrhoea.

Chronic Effects

No chronic systemic effects reported from industrial exposures.
Carcinogenicity, Mutagenicity, Teratogenicity : No Known effect.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways, product is harmful to aquatic organisms and the environment.

13. DISPOSAL CONSIDERATIONS

Aerosols should be completely empty before disposing. Recycle can if a facility is available or place can in household rubbish

14. TRANSPORT INFORMATION

UN Number: 1950
UN Proper Shipping Name: Aerosols
Class and Subsidiary Risk:2.1
Packing Group: None allocated
Hazchem Code: 2YE

Do not allow cartons to become wet. Do not store above 50°C.

Special precautions for user: Special provisions 63 (Division 2.1 Extremely Flammable), 190 Aerosol dispensers must be provided with protection against inadvertent discharge, , 327 Leaking or severely deformed aerosols must be transported in salvage packagings provided appropriate measures are taken to ensure there is no dangerous build up of pressure. Waste aerosols must not be transported in closed freight container

15. REGULATORY INFORMATION

The product is classified as Dangerous Goods Class 2.1, by the criteria of the Australian **Dangerous** Goods Code for transport by road and rail.

Hazardous according to the criteria of NOHSC

F+ Extremely Flammable

Xn: Harmful

Poisons Schedule (Aust)/Toxic Substance (NZ): Not Applicable

16. OTHER INFORMATION

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of this product. Although this information is presented in good faith and compiled from various sources,(for example and where applicable from Raw material MSDS, List of material compiled by the Australian Government Hazardous Substance Information System, Standard for the Uniform Scheduling of Drugs and Poisons, Australian Dangerous Good Code for Road and Rail, Australian Pesticides and Veterinary Medicine labelling code for Agricultural Products, believed to be accurate, Multi-Fill Pty Ltd make no representations or warranty as to the completeness or accuracy thereof. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

CONTACT POINT: Multi-Fill Pty Ltd
Technical Manager
(02) 9621 6000

APPROVED BY: Peter Exadaktylos
